



Patent
Attorney's Docket No. 027557-070

#3
13T
03-2602

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of)
Jonas PERSSON) Group Art Unit: 2681
Application No.: 09/978,007) Examiner: Unassigned
Filed: October 17, 2001)
For: COMMUNICATIONS SYSTEMS)

RECEIVED
JAN 25 2002
Technology Center 2600

CLAIM FOR CONVENTION PRIORITY

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

The benefit of the filing date of the following prior foreign application in the following foreign country is hereby requested, and the right of priority provided in 35 U.S.C. § 119 is hereby claimed:

United Kingdom Patent Application No 0025550.5


Filed: October 18, 2000

In support of this claim, enclosed is a certified copy of said prior foreign application. Said prior foreign application was referred to in the oath or declaration. Acknowledgment of receipt of the certified copy is requested.


Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

Date: January 23, 2002

By: 
Kenneth B. Leffler
Registration No. 36,075

P.O. Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620



THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

RECEIVED

JAN 25 2002

Technology Center 2600

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 10 September 2001



THIS PAGE BLANK (USPTO)

18 OCT 2000

RECEIVED BY HAND

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

HL76187/000/CIV

19OCT00 ES76958-7 D02847

P01/7700 0.00-0025550.5

2. Pate
(The)

0025550.5

18 OCT 2000

3. Full name, address and postcode of the or of
each applicant (underline all surnames)TELEFONAKTIEBOLAGET L M ERICSSON (PUBL)
SE-126-25 STOCKHOLM
SWEDENPatents ADP number (*if you know it*)If the applicant is a corporate body, give the
country/state of its incorporation

SWEDEN

7844061001

4. Title of the invention

COMMUNICATIONS SYSTEMS

5. Full name of your agent (*if you have one*)

Haseltine Lake & Co.

"Address for service" in the United Kingdom
to which all correspondence should be sent
(*including the postcode*)Imperial House
15-19 Kingsway
London WC2B 6UDPatents ADP number (*if you know it*)

34001 ✓

6. If you are declaring priority from one or more
earlier patent applications, give the country
and the date of filing of the or of each of these
earlier applications and (*if you know it*) the or
each application number

Country

Priority application number
(*if you know it*)Date of filing
(*day/month/year*)7. If this application is divided or otherwise
derived from an earlier UK application,
give the number and the filing date of
the earlier application

Number of earlier application

Date of filing
(*day/month/year*)8. Is a statement of inventorship and of right
to a grant of patent required in support of
this request? (*Answer "Yes" if:*

YES

a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

0

Description

5

Claim(s)

3

Abstract

1

Drawing(s)

1

10. If you are also filing any of the following,

Priority documents

0

Translations of priority documents

0

Statement of inventorship and right to a grant of patent (*Patents Form 7/77*)

0

Request for preliminary examination and search (*Patents Form 9/77*)

1

Request for substantive examination (*Patents Form 10/77*)

0

Any other documents
(*please specify*)

-

11.

I/We request the grant of a patent on the basis of this application

Signature

Haseltine Lake

Date

17 October 2000

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr. C.I. Vigars

[0117] 9103200

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered "Yes" Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.

COMMUNICATIONS SYSTEMS

5 The present invention relates to communications systems, and in particular, to digital communications systems.

BACKGROUND OF THE INVENTION

10 Typical current digital communication systems often use non-constant envelope modulation schemes, e.g. the new system EDGE (Enhanced Data rates for GSM Evolution) uses $3\pi/8$ -8PSK modulation. This means that some part of the information lies in the amplitude (envelope) of the transmitted signal and some part lies in the phase of the transmitted signal. In other
15 words, this is a combination of Amplitude Modulation (AM) and Phase Modulation (PM).

The non-constant envelope makes feedback power control more difficult than for modulation types with constant envelope (e.g. GMSK modulation used in GSM).
20 The reason is that the varying amplitude causes variations in power. Since the amplitude depends on the symbols that are sent, the measured power could vary between time-slots that are sent with the same nominal output power, i.e. the measured power could
25 vary although the power control signal to the amplifier in the transmitter remains constant.

SUMMARY OF THE PRESENT INVENTION

30 It is emphasised that the term "comprises" or "comprising" is used in this specification to specify the presence of stated features, integers, steps or components, but does not preclude the addition of one or more further features, integers, steps or components, or groups thereof.

35 According to one aspect of the present invention,

there is provided a method for controlling power output of a radio frequency transmitter, wherein information relating to statistical variations in the amplitude of the information signal that is to be transmitted is used to control a gain value of the radio frequency transmitter.

Embodiments of the invention described below take the statistical amplitude variation of the non-constant envelope modulation into account, and compensate for it. The control signal to the amplifier will therefore not be influenced by the amplitude variations in the modulation signal. Of course, changes in transmitter gain because of e.g. temperature variations etc. will be tracked and compensated for in the power control loop.

The principles of the invention can be applied in TDMA (Time Division Multiple Access) systems with non-constant envelope modulation. An example of such a system is the above-mentioned EDGE system.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram illustrating one embodiment of the present invention;

Figure 2 is a block diagram illustrating part of the embodiment of Figure 1; and

Figure 3 is a block diagram illustrating a second embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Figure 1 illustrates a first embodiment of the present invention which comprises a waveform generator 1 which produces a first output signal c1. The output signal c1 is supplied to a radio frequency circuit 3 which converts the signal c1 into a radio frequency signal r for transmission from an antenna 4. The

operation of the radio frequency circuit 3 is well known, and so a more detailed explanation will be omitted for the sake of clarity.

5 An attenuator 6 detects the radio frequency signal r to provide an attenuated signal a . The attenuated signal a is supplied to a power sense circuit 8 which produces a signal y which is proportional to the power of the attenuated signal a . The power sense circuit 8 may be, for example, an envelope detector.

10 A second output signal $c2$ from the waveform generator 1 is also supplied to a measurement unit 10 which operates to calculate the mean power level of the generated signal $c2$. The second signal $c2$ may be identical to the first signal $c1$, or one of the signals
15 $c1$ and $c2$ may be a time delayed version of the other. The mean power of the signal $c2$ is calculated or measured to form a mean power signal m_{mean} (in dB). The signal m_{mean} represents the mean power of the actual symbol sequence being sent in the current burst. The
20 difference between m_{mean} and a reference signal m_{ref} (in dB) results in a difference signal Δ (in dB) being output from a signal combiner 12. The value of the reference signal m_{ref} could for example be chosen to represent the mean power of a very long symbol sequence
25 in which all symbols have the same probability. The value Δ is a number which represents how much the power of the signal r can be expected to differ from a required level P_{req} , when the actual symbol sequence (burst) is sent. A signal P_{req} relating to the
30 requested power level and value Δ are supplied to a level control block 14 to form a reference value, x .

35 As mentioned above, a portion of the RF (Radio Frequency) signal, r , is taken from the radio frequency circuitry. The signal r is attenuated in the attenuator 6 to form the signal a . The signal y of the

power sense unit 18 is proportional to the power of the signal a.

5 The signal y is compared with the reference signal x by subtracting y from x using a combiner 16. The signal x is calculated (or measured) prior to the burst of information which is to be transmitted from the radio circuitry. The signal x is then present during the whole burst. The difference between the signals x and y forms an error signal e. The error signal e is
10 calculated once per data burst. The error signal e is supplied to a power controller 18, which forms a control signal u. The signal u determines the gain to be used during the next data burst of an amplifier included in radio circuitry 3. Such a system provides
15 automatic compensation of statistical variations in the amplitude of the information signal that is to be transmitted, and so these variations become "invisible" for the power control loop.

20 Figure 2 illustrates the level control unit 14 of Figure 1 in more detail. The level control unit 14 includes an adder 20 which produces a signal in decibels (dB) which corresponds to the required power level P_{req} (in dB) added to the difference value Δ (in dB). A logarithmic to linear converter 22 is provided
25 to convert the decibel (dB) signal output from the adder 20 to a linear signal.

30 Figure 3 illustrates a second embodiment of the invention in which the attenuation of the attenuator 6 is dependent of the requested nominal power level, P_{req} . Preferably the attenuation is proportional to the P_{req} signal. In this way, the attenuated power level signal a supplied to the power sense block 8 does not change much from one burst to another. This reduces the
35 dynamic range requirement of the power sense block 8.

Merits of the invention are listed below:

- Automatic compensation of statistical variations in the amplitude of the information signal that is to be transmitted, so that these variations become "invisible" for the power control loop.
- In one of the embodiments (see Figure 3) of the invention, the dynamic range requirement on the output power detector is decreased.

10

CLAIMS:

1. A method for controlling power output of a radio frequency transmitter, wherein information
5 relating to statistical variations in the amplitude of the information signal that is to be transmitted is used to control a gain value of the radio frequency transmitter.

2. A method for controlling power output of a radio frequency transmitter, the method comprising:
10 detecting output power from the radio frequency transmitter for a first data burst thereby to produce a detected power control signal;

calculating or measuring an expected mean power
15 level for an output signal for the first data burst;
calculating a difference between the expected mean power level and a reference mean power level, and producing a calculated power control signal from the said difference and a nominal power level;

20 comparing the calculated power control signal with the detected power control signal to produce a gain control signal; and

supplying the gain power control signal to the radio frequency transmitter, thereby to adjust the gain
25 thereof for at least one data burst subsequent to the first data burst.

3. A method as claimed in claim 2, wherein the detected power control signal is produced by the steps of:

30 measuring the output signal of the radio frequency transmitter, thereby to produce a measured power level signal;

attenuating the measured power level signal; and
producing a detected power control signal which is
35 proportional to the attenuated measured power level.

4. A method as claimed in claim 3, wherein the measured power level signal is attenuated by an amount proportional to the nominal power level.

5. Apparatus for controlling an output power of a radio frequency transmitter, comprising:

a detector operable to detect an output signal of a radio frequency transmitter and to produce a detected power signal indicative of the power of the output signal, the output signal relating to a first output data burst from the transmitter;

a device for calculating or measuring an expected mean power level relating to the first output data burst from the transmitter;

a power level calculation unit operable to obtain a difference between the expected mean power level and a reference power level, and to produce a calculated power control signal from the said difference and a nominal power level; and

a gain control unit for comparing the power control signal with the detected power level signal to produce a gain control signal for supply to the transmitter for at least one data burst subsequent to the first data burst.

6. Apparatus as claimed in claim 5, further comprising:

an attenuator connected to receive the output signal from the radio frequency transmitter and operable to output an attenuated signal to the detector.

7. Apparatus as claimed in claim 6, wherein the attenuator is operable to attenuate the output signal by an amount which is proportional to the nominal power level.

8. A radio frequency transmitter comprising:

a waveform generator operable to produce a

waveform signal from input data;

radio frequency circuitry connected to receive the waveform signal and operable to output a radio frequency signal, the circuitry including an amplifier having variable gain;

a detector operable to detect an output signal of a radio frequency transmitter and to produce a detected power signal indicative of the power of the output signal, the output signal relating to a first output data burst from the transmitter;

a device for calculating or measuring an expected mean power level relating to the first output data burst from the transmitter;

a power level calculation unit operable to obtain a difference between the expected mean power level and a reference power level, and to produce a calculated power control signal from the said difference and a nominal power level; and

a gain control unit for comparing the power control signal with the detected power level signal to produce a gain control signal for supply to the transmitter for at least one data burst subsequent to the first data burst.

9. A transmitter as claimed in claim 8, further comprising:

an attenuator connected to receive the output signal from the radio frequency transmitter and operable to output an attenuated signal to the detector.

10. A transmitter as claimed in claim 9, wherein the attenuator is operable to attenuate the output signal by an amount which is proportional to the nominal power level.

ABSTRACT

COMMUNICATIONS SYSTEMS

5 A method for controlling power output of a radio
frequency transmitter, wherein information relating to
statistical variations in the amplitude of the
information signal that is to be transmitted is used to
control a gain value of the radio frequency
10 transmitter.

[Fig 1]

THIS PAGE BLANK (USPTO)




Figure 1.




Figure 2.




Figure 3.

THIS PAGE BLANK (USPTO)